

# TECHNICAL DATA SHEET

## LT 4825



Komplet's LT4825 compact jaw crusher has a hydraulic adjustment system for its granulometry output. Compact, fully remote controlled and easy to transport, it allows for fast and simple set-up and use by a single operator. For onsite recycling of demolition and excavation waste, the LT4825 is the high performance solution.

### STANDARD FEATURES

- Autec remote control for all functions

### ACCESSORIES

- Magnetic roller
- Dust control system
- Side protection kit

ISUZU ENGINE		
Power	kW / Hp	21 / 28.5
Consumption	Gal / h	1.45
Cylinder	Qty	3
Cooling	Water	
PERFORMANCE*		
Production	T / h	5 - 30
Max Size	in.	3-1/8"
Standard Weight	lbs	7500
<i>*The production performance is dependent on the type and volume of material being processed as well as the size of the material produced.</i>		
WEIGHTS & DIMENSIONS		
MACHINE	Operation	Transport
Length (ft & in)	14' 8"	14' 8"
Width (ft & in)	4' 10"	4' 10"
Height (ft & in)	6' 3"	6' 3"
RUBBER TRACKS		
Length	ft & in	6' 11"
Width	ft & in	1'
JAW CRUSHER		
Crusher Dimension	ft & in	1' 7" x 10"
Jaw Adjustment	Hydraulic	
Granulometry	in	3/4 - 3-1/8
FEEDING / LOADING BELT WITH HOPPER		
Length	ft & in	5' 11"
Width	ft & in	4' 3"
Hopper capacity	yd <sup>3</sup>	1.3
Loading Height	ft & in	6' 3"
EXTRACTING BELT		
Length	ft & in	8' 3"
Width	ft & in	1' 4"
Discharge Height	ft & in	3' 8"